

US008705588B2

(12) United States Patent

Odenwalder

(10) Patent No.: US 8,705,588 B2 (45) Date of Patent: Apr. 22, 2014

(54) SYSTEMS AND METHODS FOR USING CODE SPACE IN SPREAD-SPECTRUM COMMUNICATIONS

(75) Inventor: **Joseph P. Odenwalder**, Rancho Santa

Fe, CA (US)

(73) Assignee: QUALCOMM Incorporated, San

Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 790 days.

(21) Appl. No.: 10/783,771

(22) Filed: Feb. 20, 2004

(65) **Prior Publication Data**

US 2004/0228389 A1 Nov. 18, 2004

Related U.S. Application Data

(60) Provisional application No. 60/452,790, filed on Mar. 6, 2003, provisional application No. 60/470,770, filed on May 14, 2003.

(51) Int. Cl. *H04B 1/69* (2006.01) *H04B 14/06* (2006.01)

(52) **U.S. CI.** USPC**375/130**; 375/246

(58) Field of Classification Search
USPC 375/130, 134, 137, 145, 149, 246, 253,

375/240.1, 11; 341/3, 9, 82, 83, 143, 39; 714/755, 810; 382/234; 332/108, 119, 332/151, 109; 329/316

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

2,149,518 A 3/1939 Frank, Sr. 3,470,324 A 9/1969 Harmuth

4,768,023 A	8/1988	Xie
5,280,472 A	1/1994	Gilhousen et al.
5,394,433 A	2/1995	Bantz et al.
5,406,585 A	4/1995	Amitava et al.
5,463,342 A	10/1995	Guard
5,483,557 A	1/1996	Webb
5,490,165 A	2/1996	Blakeney, II et al.
	(Continued)	

FOREIGN PATENT DOCUMENTS

CN 1166094 11/1997 CN 1263675 8/2000 (Continued)

OTHER PUBLICATIONS

Oguz Sunay M. et al., "Provision of Variable Data Rates in Third Generation Widebands DS CDMA Systems." Wireless Communications and Networking Conference, 1999, Sep. 21, 1999, pp. 505-509.

(Continued)

Primary Examiner — Khai Tran (74) Attorney, Agent, or Firm — Eric Ho

(57) ABSTRACT

Systems and methods for improving the performance of direct-sequence spread-spectrum communication systems. In one embodiment, a system comprises at least one communication channel that utilizes two different orthogonal spreading codes and corresponding portions of the available orthogonal code space. Portions of the data processed by the communication channel are demultiplexed into different streams and covered with corresponding, different orthogonal spreading codes. The streams covered by the different orthogonal codes are then combined and transmitted via the same communication channel. One embodiment utilizes at least two different Walsh codes of different lengths (+– and ++–) in order to make use of the three quarters of the Walsh space not utilized by low-rate legacy channels.

46 Claims, 5 Drawing Sheets

